

MAIN ENGINE

NORMAL CONDITION

CYLINDER		AVE	1	2	3	4	5	6
PMAX bar		97.7	98	98	97	98	98	97
PCOMP bar		66.2	66	67	66	66	66	66
FUEL	Actuator		4.3	3.2	2.7	3.3	3.3	2.7
PUMP	pump mark	55.8	56	56	56	56	56	55
Exh. Gas Temp. Cyl. Outlet C		310	315	310	310	310	315	310
C.F.W. Temp. Cyl. Outlet C		80	80	80	80	80	80	80
P.C.O Temp. Cyl. Outlet C		50	50	50	50	50	50	50

OVER HEATING CONDITION

CYLINDER		AVE	1	2	3	4	5	6
PMAX bar		97.7	98	98	97	98	98	97
PCOMP bar		66.2	66	67	66	66	66	66
FUEL	Actuator		4.3	3.2	2.7	3.3	3.3	2.7
PUMP	pump mark	55.8	56	56	56	56	56	55
Exh. Gas Temp. Cyl. Outlet C		345	350	350	355	345	340	340
C.F.W. Temp. Cyl. Outlet C		90	92	90	90	92	88	88
P.C.O Temp. Cyl. Outlet C		50	50	50	50	50	50	50