

## **DISCHARGING INTRUCTION**

PORT : PONTIANAK VOY : 27/D/2015

DATE : 22TH.AUGUST 2015

CARGO : ADF

STOWAGE: 1CROSS, 2CROSS, 3CROSS, 4CROSS.

QUANTITY: BL: 3590.045 KL 15°C.

- 1. All the time think for safety fist.
- 2. All the times mooring lines tighten.
- 3. To prevention of pollution.
- 4. All the times scuppers effectively plugged.
- 5. Make sure the galley doors/ hole closed during cargo operation.
- 6. Make sure all valves/suction valves in shut condition before connecting the hose, checked one more time for drain valves is shut condition in pump room.
- 7. Before starting for connection the hose,make sure the hose clean from the previous cargo. SEQUENCES DISCH:
- 10. DISCHARGING SOLAR COT 1Centre, 2 centre, 3 centre, 4 centre till stripping level N continue disch wing tank start from 1W,2W,3W,& 4W till dry
- 10. No leaked all the times shall be checked lines, valves or other prior discharging operation.
- 11. Flow rate the **Dischaging Rate maximum is 300 M3/Hrs**
- 12. Keep control the cargo level by Sounding measure and avoid cargo over flow.
- 13. Keep the vessel upright all the time, no more 0,5 degree list of the vessel during cargo operation.
- 14. Noted all necessary activity during on Port in the Cargo Oprtn & Port Log Book.
- 15. After completed discharge, make sure any the tanks must be **empty and dry**, and than Blowing W/Air or flushing W/Sea Water the discharge pipe line by Ship Cargo pump.
- 16. When hose disconnected, make sure no pressure on the line or hose and the hose line shall be dry.
- 17. After disconnected make sure the all valves is fully shut.
- 18. During Cargo Operation do not left the deck for long time at lass inform to Ch. Officer.
- 19. Call Ch. Off if any abnormally situation
- 20. GOOD LUCK, MAY GOD BLESS US ALWAYS.

## REMARKS;

- DILARANG MENGGUNAKAN \* HP \* SELAMA DALAM OPERASI CARGO (MUAT/BONGKAR) DI MAIN DECK DAN SEKITARNYA

Prepared By:

	<u>SUTYAGUS WIDODO</u>
	Ch. Officer
2 <sup>nd</sup> Officer	
3 <sup>rd</sup> Officer	