

Member Panel | Abstract submission

Upload Abstract  
Abstract

Your abstract has been received, please submit your full paper !

Paper Themes  
**ELECTRICAL ENGINEERING & INFORMATION TECHNOLOGY**

Article Title  
**ANALYSIS OF THE EFFECT OF CONDITON OPERATIONAL OF VESSEL AND GENERATOR OPERATIOI**

Full Author (Exp : Rizky Ajie Aprilianto, Septian EP)  
**LUTFI ADI PRABOWO, ABDI SENO, ADI OKTAVIANTO, DARUL PRAYOGO**

PERBEDAAN\_SKA....docx    Permenristek Dikti....pdf    Show all



PROCEEDINGS OF  
**THE 8<sup>th</sup> ENGINEERING  
 INTERNATIONAL  
 CONFERENCE**

"Concept and Application of Green Technology"

Editor-in-chief:  
 Dr. Feddy Setio Pribadi, S.Pd., M.T.

 **Faculty of Engineering**  
 Universitas Negeri Semarang  
 Faculty of Engineering Deanery Building, Sekaran, Gunungpati, Semarang,  
 50229

**Editorial Board**

**Director:**  
 Dr. Nur Qudus M.T., IPM.  
 (Dean of the Faculty of Engineering, Universitas Negeri Semarang)

**Deputy Director:**  
 Dr.-Ing. Dhidik Prastyanto S.T., M.T.  
 (Deputy Dean for Academic Affairs, Faculty of Engineering, Universitas Negeri Semarang)

**Editor-in-chief:**  
 Dr. Feddy Setio Pribadi, S.Pd., M.T.

**Deputy Editor-in-chief:**  
 Sita Nurmasiah, S.S., M.Hum.  
 Putri Khoirin Nashiroh, S.Pd., M.Pd.

**Editors:**  
 Adhi Kusumastuti, S.T., M.T., Ph.D.  
 Dr. Rini Kusumawardani, S.T., M.T., M.Sc.  
 Dr. Alfa Narendra, S.T., M.T., ATM.  
 Dhoeni Harianto, S.T., M.T., M.Sc.  
 Haniff Prasatiawan, S.T., M.Eng.  
 Ahmad Fashiha Hastawan, S.T., M.Eng.

**Co-Editors:**  
 Edi Sarwono, S.Pd., M.T.  
 Nur Aziz Salim, S.T., M.Eng.  
 Esa Apriankar, S.T., M.T.  
 Anan Nugroho, S.T., M.Eng.  
 Vera Noviana Sulistyawan, S.T., M.T.  
 Riska Dami Ristanto, S.Pd., M.Pd.  
 Fitria Ekarni, S.Pd., M.Pd.



**Table of Contents**

Modulus of Elasticity and Tensile Strength on Textile Reinforced Concrete Using Cantala Fiber (Agave Cantala Roxb).....	1
Application 3D Printing in Interior Car.....	8
The coloring quality of cement's packaging paper waste using the extract of tea leaves (Camellia sinensis).....	16
The Analysis of Soil Chemical and Mineralogy to Compression Strength of Expansive Soil with Sugar Cane (Study Case: KM 49-Godong, Grobogan District).....	21
Development of Hybrid System for Green Transportation.....	27
The effect of composition of glutinous rice flour in making batik with cold wax.....	42
Alternative Flood Management Modeling in Semarang Banger River Basin.....	47
Industrial Mapping in Sulawesi-Maluku-Papua Corridor.....	54
Performance Analysis of Road Caused by Light Rail Transit Plan (Study case: Simpang Lima-Terminal Pongoran Semarang LRT Corridor).....	59
The Development of Landslide Potential Investigation Technology of Using Schlumberger Geo-Electrical Method.....	65
Financial Analysis and Institutional Scheme of Port-City Conceptual Design.....	73
The Pattern of Load - Settlement Curve in The Bore Pile Testing on Silty Clay in The Testroom Hotel and Apartment project, Semarang.....	79
Analysis of Limit Ductility of Column Basement on Building 22 Floors with Ahaqun on Hard Soil Location.....	96
System Strengthening Scientific Digital Based in Faculty of Engineering.....	112
Solar Cell Telemetry - Based Early Detection Device Development Considering of Forest Fire.....	120
Determination of Dengue Hemorrhagic Fever Vulnerable Areas with Decision Support Systems Using Profile Matching.....	128
Feasibility Analysis of E-Label Batik Application as a Model of Batik Protection in Pekalongan City.....	139
Method Productivity Delay Model for Monitoring Worker Waste on Concrete Casting: a Case Study.....	148
Eye Tracking: The Visualization of Consumer Interest to Product in E-commerce.....	154
Application of Electronic and Secure Automatic and Comfortable Automatic Parking Model.....	162
Analysis of Temporary Hanger Planning Problems in Bridge Work Using Cross Girder.....	165
An Analysis of Load Imbalance on The Neutral Wire Current in E11 Building and The Deanery Building of The Engineering Faculty of Universitas Negeri Semarang.....	169
Location-Based Tree Identification Information System.....	177
Vessel Operational Impact and Generator Operation Toward Electrical Power Load in Mv. DR-02.....	185



## Vessel Operational Impact and Generator Operation Toward Electrical Power Load in MV-DK-02

Lutfi Adi Prabowo<sup>1</sup>, Abdi Seno<sup>2</sup>, Adi Oktavianto<sup>3</sup>, Darul Prayogo<sup>4</sup>, Dwi Prasetyo<sup>5</sup>

<sup>1</sup>Technical cadet of Politeknik Ilmu Pelayaran Semarang, Semarang, Indonesia.  
<sup>2</sup>Technical Lecturer of Politeknik Ilmu Pelayaran Semarang, Semarang, Indonesia.

Email: darulprayogo@yahoo.co.id

**Abstract.** Electrical Power Load is everything that heated and occurred by electrical power. The purpose of this research is to analyze the operational condition of vessel and generator operation toward electrical power load on board. The research used quantitative method with application program to analyze the correlation and the impact between independent variable and dependent variable from the electrical power load data. The result of the research done by the researcher on board in X1 (operational condition of vessel) look negative effect toward Y (electrical power load) for 4.2 %. X2 (generator operation) look positive impact toward Y (electrical power load) for 1.1 %. Together, it created positive impact for 4.4 %.

**Keywords:** Vessel operational condition, generator operation, electrical power load, SPSS.

### 1. Foreword

Operational is the border and guideline to do an activity. Vessel is a moda to carry the cargos, passengers, or bulk such as coal in order to industrial needs. Vessel operational is a vessel activity in a various condition when the vessel is on sea. [1] Generator operation is an interconnection between several generators in a unit, single or together to carry the burden. The generator will be paralleled to be manually synchronized or automatic, in order to get a bigger power. [2]

The definition of AC generator is a machine that converse mechanic energy (kinetic) to be electric energy with the help of magnetic induction. The energy transformation happened because the change of the magnet medium to the coil/anchor (the place where the voltage risen toward generator). [2]

Electricity load is everything which burdened and need electrical power. Electricity load is a electric motor, lighting and the equipment that connect to the source. Electrical Power is a energy accumulation that absorbed or resulted in a circuit. The energy source such as electrical voltage will result electric power, while the connected load will be absorbed with that voltage. The electric power is an energy consumption level in the electric circuit. [3]

When the vessel anchor, the condition of a generator is fully loaded 200kW, therefore, it will experience overloaded capacity and probably cause a blackout. In other chance, 2 generator paralleled and fully loaded for each generator 160 kW for the discharging process and using 4 crane in order to finish it quickly. Those 3 generators will be operated together with the load for each generator is between 160 kW until 240 kW. When the crane operated, the wait motor shows the number that always move. To anticipate anything, the awareness is needed by the engineers, to order the deck department to use 3 cranes. The fuel usages will be increased if the loading discharge delayed and the

operational time of the diesel generator. The condition of Vessel Operation and Generator Operation toward Electrical Power Load in MV-DK-02 is a subject to be studied.

### 2. Literature Review

#### 2.1. Literature Review

Vessel operation is the implementation from the vessel activity plan when operated, in order to reach the purpose as a sea transport moda that have implemented based on the Regulation. [1] There are several conditions in the vessel operation of MV-DK-02, which are:

1. Berthing is a condition when the vessel berth on the port to do the loading and discharging activity.
2. Maneuver is a vessel ability to bend and turn around when sailing in the limited water area around the port.
3. Stalling is a vessel condition when doing a voyage from the departure port toward the arrival port from the finished maneuver until the maneuver on the sea to wait for the berthing line-up on the port.
4. Drop anchorage is a vessel condition when the anchor drop on the sea to wait for the berthing line-up on the port.

AC Generator is a power generator or called alternator that has function to convert the mechanical energy (kinetic) to electric energy with magnet induction as the medium. [2]

Generator operation is a generator condition that operated to be resulted voltage and power need to the electrical load used. [2] There are 2 modes on generator operation or generator operation on board to electric resources and power load used to machining aids, which are:

1. Operation mode single generator  
 Operation mode single generator is a 1<sup>st</sup> operation generator to the needs of electric load needed by the generator. The usage of single generator operation is when the vessel anchor or without overload.
2. Operation mode parallel generator  
 Irving (1991) stated that parallel generator operation is a condition of two or more generators, so each of the current flow to the load. [2] The advantage of parallel generator on board is:
  - 1) To gain greater power.
  - 2) The certainty of power capacity.
  - 3) To guarantee the continuity of electrical power availability.
  - 4) To contain the developed load.

Electricity load is anything that needs electricity power. Electricity load is a electric motor, lighting and the equipment connected with the source. Electrical power is the energy about absorbed and resulted in the circuit with energy consumption level of electric circuit.

#### 2.2. Framework

Framework is the relation between the variables arranged by several described theories. The framework made by the position based on the relevant theories so the problem in the research will be solved.




Figure 1. Framework of the Research

### 3. METHODS

#### 3.1. Research Methods

Research method is the scientific way to gain the data with certain purposes and usages. Based on the definition, there are 4 keywords that need to be considered, which are scientific, data, purpose and usage. [4]

Quantitative method with descriptive analysis to strengthen the findings, data analysis and descriptive will help to test the relation between independent variable which are vessel operational condition and generator operation toward related variable which is electrical power load

#### 3.2. Time and Place for the Research

The research done when on MV-DK-02. It is one of the Bulk Carrier vessel on PT. Karya Sumber Energi.

#### 3.3. Data Need

Information gained toward certain measurement, order to be base on arranging logical argumentation to become fact. The fact is the truth tested empirically, which is from data analysis.

1. Primary data is data gained directly from the first source through the interview result, inspected and the characteristics were noted toward the research object.
2. Secondary data is the data provided by the writer, gained by the writer, other than the subject of the research.

#### 3.4. Data Gained Method

1. Observation is an inspection done by the available situation, spontaneous and scientifically, and the result of the inspection will be summarized and the data gained will be objective.
2. Interview is a process to gain of the research purpose with interviewing between the researcher and the stakeholders. [5]
3. Documentation is gaining with learning the archives and letters inside the engine room, especially about diesel generator journal in the section of electrical power load.

#### 3.5. Data analysis technic

Data analysis is a process of find and arranging the data systematically from the interview, field note, and other material, so it will be easier to be understood and the founding will be informed to other persons. [6]

##### 1. Descriptive analysis

Quantitative method is used to tell the problem is SPSS.

##### 2. Validity Indicator Test

Validity test is used to know the progress of the question to define a variable. The test technic for validity test is using Bivariate Pearson correlation and Corrected Item-Total Correlation. [7]

##### 3. F Test

F test is used to test the truth of alternative hypothesis, is the model chosen by the researcher correct. Goodness of Fit is all of the independent variable's impact toward the dependent variable. Ho:  $\rho = 0$  (weak relation)

Hi:  $\rho \neq 0$  (not-weak relation)  
 If the significant value (p-value) is  $< 0.05$  (the significant is 5%) and/or the F value  $>$  F table, the summary is Ho denied and Ha accepted. Meanings, there is the same effect of independent variable toward dependent.

##### 4. Multiple Linear Regression Analysis

Multiple Linear Regression Analysis is used to predict something, where in the model there is a dependent variable and independent variable. [8] The impact of independent variable toward the dependent variable is the similar regression used as below:

$$Y = a + \beta_1 X_1 + \beta_2 X_2$$

Where:

- Y : Electrical Power Load
- X1 : Vessel operation condition
- X2 : Generator operation
- $\beta_1, \beta_2$  : Standard coefficient regression
- a : Constant

Hypothesis formula:

- Ho:  $\beta_1 = 0$ ; there is no independent impact toward dependent variable
- Ha:  $\beta_2 = 0$ ; there is independent variable impact toward dependent variable

### 4. Discussion

#### 4.1. Research Result

This descriptive variable to explain variable data "Y" which is electrical power load. X1 dan X2 Variable is the ordinal data from the operational condition.

##### a. Mean, Median, Modus, Maximum dan Minimum

Table 1. Electrical Power Load

Mean	132,29
Median	140,00
Mode	140
Minimum	80
Maximum	180

The usage of electrical power load in MV-DK-02 gained by the mean result 132.29 kW. While the median from the total electrical power load that oftenly used is 140 kW. The mode of electrical power load above is 140 kW.

The maximum value gained is 180 kW is the biggest load usage when doing the research. The minimum electrical power load gained is 80 kW which the usage is barely used when the generator operated.

##### b. Frequent




Figure 2. Frequent Diagram



The usage of electrical power load often shown in the usage of electrical power load, which is 140 kW. Followed 120 kW, 80 kW, dan 100 kW, in usage usually of the load 110 kW and 180 kW with frequent 1.

4.2. Test the quality of the validity test electrical power load

Table 2. KMO and Bartlett's electrical power load  
 Kaiser-Meyer-Olkin Measure of Sampling Adequacy

0,552

Gained KMO value for the indicator test used to measure the variable of electrical power load is 0.552 because the value > 0.5 for the contentment of the sample is fulfilled.

Table 3. Component matrix

KON_OPE_KAPAL	,633
OPE_GENERATOR	,680
BEBAN_DAYA_LISTRIK	,582

The indicators used to arrange the variable stated valid because in the table matrix component the value is > 0.5 and the load factor is not < 0.5.

4.3. Model Fit Test

a) The correlation vessel operational condition analysis with electrical power load



Figure 3. Scatter Graphic with Correlation Plot X1 with Y

Table 4. Correlations Variabel X1 dengan Y

	KON_OPE_KAPAL	BEBAN_DAYA_LISTRIK
KON_OPE_KAPAL	1	-.205
PAL		,238
N	54	35
BEBAN_DAYA_LISTRIK	-.205	1
N	35	35

Gained the Vessel Operational Condition (X1) with the Electrical Power Load (Y) in the scatter plot to the left means "negative". The result of Pearson Sig correlation = 0.238 (23.8%) > 5% meanings Ho accepted and H1 denied. There is the relation between Vessel Operational Condition (X1) and

Electrical Power Load (Y) that makes it weak. In order to strengthen the statement, it is gained the empiric correlation value (p1) = -0.205. The value shows the correlation between X1 and Y is negative.

b) The correlation of generator operation (X2) analysis with electrical power load (Y)



Figure 4. Scatter Graphic Correlation Plot X2

Table 5. Correlations Variabel X2 with Y

	OPE_GENERATOR	BEBAN_DAYA_LISTRIK
OPE_GENERATOR	1	,104
ATOR		,552
N	54	35
BEBAN_DAYA_LISTRIK	,104	1
N	35	35

Generator Operation (X2) with Electrical Power Load (Y) in scatter plot on the right side with "positive" value. The result of Pearson Sig Correlation = 0.552 (55.2%). The value of 55.2% > 5% means that Ho accepted and H1 denied. The connection between X2 and Y is weak. To strengthen that statement, gained the empiric correlation value (p2) = 0.104 the value shows the correlation between X2 and Y positive.

4.4. Regression analysis

Linear regression analysis is the relation between one independent variable (X) with dependent variable (Y). The positive value or negative to predict the value from dependent value if the independent variable value experience ascension or downgrade. The data used has interval score or ratio. The formula of simple linear regression is:  $Y = a + \beta X$

Hypothesis 1: Electrical Power Load (Y) affected by Vessel Operational Condition (X1).




Figure 5. Hypothesis X1 toward Y

Ho:  $\beta_1 = 0$ ; (Non linear equality or X1 is not impactful toward Y)  
 H1:  $\beta_1 \neq 0$ ; (Linear equality or X1 impactful toward Y)

Table 6. Coefficients X1 and Y

Model	Unstandardized Coefficients		Standardized Coefficients		t	Sig.
	B	Std. Error	Beta			
1 (Constant)	5,351	1,720			3,111	,004
BEBAN_DAYA_LISTRIK	-.015	,013	-.205		-1,201	,238

Unstandardized Coefficients (B) gained value  $a = 5.351$  and  $\beta_1 = -0.015$ . The equity formed:  $Y = 5.351 - 0.015 X_1$ . To test the equity above whether accept or deny the hypothesis told, there is a distribution "F" toward output table ANOVA.

Table 7. ANOVA X1 and Y

Model	Sum of Squares	Df	Mean Square	F	Sig.
1 Regression	4,083	1	4,083	1,442	,238 <sup>a</sup>
Residual	93,460	33	2,832		
Total	97,543	34			

F value = 1,442 and Sig = 0,238 (23,8%) > 5% meanings Ho accepted and H1 denied. The equity is linear or X1 have negative impact toward Y (negative sign taken from regression coefficient). To know how valuable the impact X1 toward Y, you could see Determination Coefficient (R Square) toward Model Summary.

Table 8. Model Summary X1 dan Y

Model	R	R Square	Adjusted R Square	Std. Error of the Estimate
1	,205 <sup>a</sup>	,042	,013	1,683

Value  $R^2 = 0.042$  or 4.2% shows that Operational Condition variable of Vessel (X1) contributes toward the Electrical Power Load (Y) for 4.2%. There are 95.8% is still there electrical power load (Y) affected by other variable.

Hypothesis 2: The result of electrical power load (Y) affected by generator operation (X2) of vessel



Figure 6. Hypothesis X2 toward Y

Ho:  $\beta_2 = 0$ ; (Non-linear equality or X2 is not related toward Y)  
 H1:  $\beta_2 \neq 0$ ; (Non linear equality or X2 is not having impact toward Y)

Table 9. Coefficients X2 dan Y

Model	Unstandardized Coefficients		Standardized Coefficients		T	Sig.
	B	Std. Error	Beta			
1 (Constant)	1,739	,729			2,385	,023
BEBAN_DAYA_LISTRIK	,003	,005	,104		,601	,552

Unstandardized Coefficients (B) obtained  $a = 1.739$  and  $\beta_2 = 0.003$ . The equity formed is:  $Y = 1.739 + 0.003 X_2$ . To test the equity, whether accept or deny the hypothesis told, the F distribution determined on output table ANOVA as follow:

Table 10. ANOVA X2 and Y

Model	Sum of Squares	Df	Mean Square	F	Sig.
1 Regression	,184	1	,184	,362	,552 <sup>a</sup>
Residual	16,787	33	,509		
Total	16,971	34			

Value  $F = 0.362$  and Sig = 0,552 (55,2%). Sig value 55,2% > 5%, meanings Ho accepted and H1 denied. The equity is not linear or X2 have positive impact toward Y (positive sign taken from regression coefficient).

To know how big the value of X2 toward Y, it could be seen from Determination Coefficient (R Square) toward Model Summary as follow:

Table 11. Model Summary X2 and Y

Model	R	R Square	Adjusted R Square	Std. Error of the Estimate
1	,104 <sup>a</sup>	,011	-,019	,713

Value  $R^2 = 0.011$  or 1.1%, show that the variable of Generator Operation (X2) contribute toward the data of Electrical Power Load (Y) for 1.1%. There are 98.9% data of electrical power load (Y) affected the other variable.

4.5. Multiple Linear Regression Analysis

Hypothesis 3: Result of Electrical Power Expense data (Y) is affected vessel operational condition (X1), and generator operation (X2)

$Y = a + \beta_1 X_1 + \beta_2 X_2$




Figure 7. Hypothesis X1 and X2 to Y

Ho:  $\beta = 0$ ; (Equation is not linear or X1, X2, is not affecting Y)  
 H1:  $\beta \neq 0$ ; (Equation linear or X1, X2, affecting Y)

Table 12. Coefficients X1, X2 and Y

Model	Unstandardized Coefficients		Standardized Coefficients	T	Sig.
	B	Std. Error	Betas		
(Constant)	136,989	16,831		8,139	,000
KON_OPE_VES	-2,529	2,383	-,190	-1,061	,296
SEL_OPE_GENERAT	1,694	5,712	,053	,297	,769

Unstandardized Coefficients (B) is obtained value  $a = 136,989$  and  $\beta_1 = -2,529$ ;  $\beta_2 = 1,694$ . Equation that is formed is:  $Y = 136,989 - 2,529X_1 + 1,694X_2$ . For examining the equation whether accepting or rejecting hypothesis which is mentioned calculation "F" distribution is conducted on output table ANOVA.

Table 13. ANOVA X1, X2, and Y

Model	Sum of Squares	Df	Mean Square	F	Sig.
1 Regression	765,947	2	382,973	,745	,483 <sup>b</sup>
Residual	16451,196	32	514,100		
Total	17217,143	34			

Value  $F = 0,745$  and  $Sig = 0,483$  (48,3%). Value  $Sig$  48,3% > 5%, which means  $H_0$  is accepted and  $H_1$  is rejected. That equation is not linear or  $X_1, X_2$  is not affecting  $Y$ . For figuring out how much  $X_1, X_2$  contribute on  $Y$  we can see Determination Coefficient (R Square) on Summary Model.

Table 14. Model Summary X1, X2, dan Y

Model	R	R Square	Adjusted R Square	Std. Error of the Estimate
1	,211 <sup>a</sup>	,044	-,015	22,674

Value  $R^2 = 0,044$  or 4,4%. That value showing us that variable of Vessel operational condition ( $X_1$ ), Generator operation ( $X_2$ ) contributes simultaneously on Electrical power expense result ( $Y$ ) of 4,4 %. With that result there is still 95,6% of Electrical power expense data ( $Y$ ) which is affected by another variable.

4.6. Summary

$X_1$  variable is an ordinal data which is not valuable and description from each condition of a operational condition vessel when is a berthing condition for cargo operation, maneuvering, when sea passage (sailing), anchoring for cargo loading.  $X_2$  variable is an data from each generator operation which is a single operation (run 1), parallel (run 2), and parallel (run 3). Electrical power expense for finding average value, middle value, and expense value that almost has the same result and often noted on expense which is used from all vessel operational conditions, and all generator operation condition in every operating electrical generator. The use of electrical power expense obtain an average (mean) 132,29 kW, middle value (median) from overall 140 kW, often-appear value (mode) 140 kW, maximum value 180 kW and minimum value 80 kW expense usage of generator. Usage frequency of electrical power expense with using often appear 140 kW, 160 kW, 120 kW, 80 kW and 100 kW expense is usually found for 110 kW and 180 kW with frequency 1 for each expense.

4.6.1. Correlation between variable

Correlation coefficient value person sig  $X_1$  of 0.238 vessel operational condition affect toward electrical power expense of 23,8 %. Thus it can be concluded that vessel operational condition toward electrical power expense is weak (affected).

Correlation coefficient value person sig  $X_2$  of 0.552 generator operation affect toward electrical power expense of 55,2%. Thus it can be concluded that operation of generator affect the electrical power expense, which is not weak.

4.6.2. Regression between variable

Regression equation value is  $Y = 5,351 - 0,015 X_1$ . Then  $X_1$ ,  $R$  Square value is 0,042, condition of operational vessel ( $X_1$ ) affect the variable related to electrical power expense ( $Y$ ) up to 4,2 % while the rest 95,8 % affected by another variable.

Regression equation value is  $Y = 1,739 + 0,003 X_2$ . Then  $X_2$ ,  $R$  Square value is 0,011, generator operation ( $X_2$ ) affect variable related to electrical power expense ( $Y$ ) up to 1,1 % while the rest 98,9 % affected by another variable.

Value ( $X_1$  dan  $X_2$ )  $R$  Square is 0,044, independent variable of operational vessel condition ( $X_1$ ) and independent variable of generator operation ( $X_2$ ) can affect variable toward electrical power expense ( $Y$ ) up to 4,4 %, while the rest 95,6 %. Thus operational vessel condition and generator operation toward electrical power expense has a low impact. And the rest 95,6% affect another independent variable.

From the calculation related is 95,6%. The use of electrical power expense may affected by independent variable, for instance electrical flow, generator expense, inductive expense. Another expense is electrical motor, transformer, relay and all wire coil expense that can cause electrical power unstable. Electrical motor which has been used for a long time and cause the expense to change not according to name plate on expense usage, power factor or the flow entering electrical motor. Can be caused also by loss volt that flowing from electrical generator to the active electrical equipment.

5. Conclusion

5.1. Conclusion

Based on analysis result and summary can be taken conclusion as follows:

1.  $X_1$  (vessel operational condition) affects (negative) toward  $Y$  (electrical power expense) regression equation  $Y = 5,351 - 0,015 X_1$ . Value of  $R$  square is 4,2 %.
2.  $X_2$  (generator operation) affect (positive) toward  $Y$  (electrical power expense) regression equation  $Y = 1,739 + 0,003 X_2$ . Value of  $R$  square is 1,1 %.
3.  $X_1$  (vessel operational condition) and  $X_2$  (generator operation) affect (positive) toward  $Y$  (electrical power expense) regression equation  $Y = 136,989 - 2,529X_1 + 1,694X_2$ . Value of  $R$  square is 4,4%. And the rest 95,6% affect another variable which related to the use of electrical power expense.

5.2. Suggestion

Based on the result of the conducted analysis, thus the suggestion from the experiment done as follows:

1. If the condition of operational vessel when sailing only need less power by using only one generator to save the fuel and also running hour from the generator diesel engine.
2. When on cargo operation the vessel need extra power than 2 or 3 generators are needed, and in watchkeeping time the communication between engine room and bridge watchkeeper should be maintained. So that the engine room watchkeeper can rest the diesel generator when cargo operation to decrease the power consumption.
3. For the next author, the author is suggested to examine other variable than  $X_1$  and  $X_2$  for figuring out whether it would be support or weaken the examination that the author did.

References

- [1] Nimpuno, Harjojo Bono, 2014, *Kamus Bahasa Indonesia Edisi Baru*, Jakarta: Tim Pandom Media Nusantara, Pandom Media Nusantara.
- [2] Kosow, L. Irving, 1991, *Electric Machinery And Transformer*, Germany.
- [3] Malana M Yusuf, 2017, *Artikel Teknologi – Pengertian Beban Resistif, Induktif, Dan Kapasitif Pada Jaringan Listrik AC*. <http://artikel-teknologi.com/pengertian-beban-resistif-induktif-dan-kapasitifpadajaringanlistrik-ac>
- [4] Sugiyono, 2016, *Metode Penelitian Kuantitatif, Kualitatif dan R&D*, Bandung: PT Alfabeta.
- [5] Sugiyono, 2015, *Memahami Penelitian Kualitatif*, Bandung: Alfabeta.
- [6] Kamus besar bahasa Indonesia (KBBI), (<http://web-id.implementasi.com>), Diakses pada tanggal 16 Mei 2019.
- [7] Sajurweni, V. Wiratna, 2014, *Metode Penelitian Lengkap, Praktis Dan Mudah Dipahami*, Yogyakarta: Pustaka Baru Press.
- [8] Santoso, Singgih, 2017, *Menguasai Statistik Dengan SPSS 24*, Jakarta: PT Elex Media Komputindo



Simpan Otomatis MATI USER PASS - Mode Kompatibilitas - Disimpan ke Mac saya

Beranda Sisipkan Gambar Desain Tata letak Referensi Surat Peninjauan Tampilan Beri tahu saya

Calibri (Bo... 11 A<sup>+</sup> A<sup>-</sup> Aa B I U X<sub>2</sub> X<sup>2</sup> A<sup>+</sup> A<sup>-</sup> Aa BbCcDdEe AaBbCcDdEe AaBbCcD AaBbCcDdEe Normal Tidak Ada Sp... Judul 1 Judul 2 Panel Gaya Dikte Editor

<http://103.23.102.226/eic/>  
<http://103.23.102.226/eic/member/dashboard>  
<http://103.23.102.226/eic/home#>

USER  
darul  
darul

Phone Number  
Alfa Faridh Suni +62 856-4084-5672  
Arimaz Hangga +62 856-3210-670  
Ari Dwi Nur I. +62 818-0483-3667

Halaman 1 dari 1 23 kata Bahasa Indonesia Fokus 109%



Dear colleagues,

We cordially invite you to join in **the 8th Engineering International Conference (EIC)** conducted by Faculty of Engineering UNNES which will be held on October 16th, 2019. Outstanding selected articles will be published in Scopus - indexed journal. Please visit <http://eic.ft.unnes.ac.id> for the conference details.

**The 8<sup>th</sup> Engineering International Conference**  
Faculty of Engineering, Universitas Negeri Semarang, Indonesia  
October 16<sup>th</sup>, 2019

**KEYNOTE SPEAKER**

**Prof. Nadja Dr. Zaidi Umar Bin Zakaria**  
School of Electronic and Electrical Engineering, Universiti Teknologi Malaysia, Malaysia

**Dr. Karapınar Başgözü**  
Department of Industrial Engineering, Koçubiç, Ankara, Turkey

**Dr. Wang Qi Yun**  
Department of Learning Sciences & Technologies (LST), Nanyang Technological University, Singapore

**Dr. Ing. Didiok Prastipato, S.T., M.T.**  
Department of Electrical Engineering, Faculty of Engineering, Universitas Negeri Semarang, Indonesia

**CALL FOR PAPERS**  
Topics of interest include, but are not limited to, the following:  
1. Chemical Engineering  
2. Electrical Engineering and Information Technology  
3. Mechanical And Manufacture Engineering  
4. Civil Engineering & Architect

**REGISTRATION FEE**

	Indonesia	Overseas
Penerima	IDR 1.500.000	USD 150
Co-ordinator	IDR 1.000.000	USD 100
Participant	IDR 1.000.000	USD 100
Mini Symposium	IDR 350.000	USD 35

**PUBLICATION**  
1. International Journal of Innovation and Learning (Scopus Indexed)  
2. Journal of Physics: Conference Series - IOP Publishing (Scopus Indexed)  
3. Mahasarabham International Journal of Engineering Technology (International Journal)  
4. Jurnal Bahan Alam Terbarukan (National Accredited Journal)  
5. ISSN Conference Proceedings  
6. Mini Symposium Conference Proceedings

\*Please go to the conference website for further details.

**Supported by:**

**UTM**  
Journal of Physics Conference Series  
IOP Publishing  
Innovation and Learning

**NANYANG TECHNOLOGICAL UNIVERSITY**  
SINAPULS

**VENUE**  
Deanery Building, Faculty of Engineering  
Universitas Negeri Semarang, Kampus Sekeloa Gunungpati  
Semarang, Central Java, Indonesia 50229

**CONTACT**  
E-mail: [eic.ft@mail.unnes.ac.id](mailto:eic.ft@mail.unnes.ac.id)  
Website: [eic.ft.unnes.ac.id](http://eic.ft.unnes.ac.id)  
CP: Pusti Rhoirini MT (+62 856-4669-6490)  
Ari Dwi Nur I M (+62 810-0483-3667)  
Alfa Faridh Smiti (+62 856-4084-5672)  
Arizma Hangga (+62 856-3210-670)

**IMPORTANT DATES**  
Abstract deadline : 24 August 2019  
Full paper deadline : 25 August 2019  
Paper Acceptance Notification : 5 September 2019  
Camera ready deadline : 30 September 2019  
Registration & Payment Deadline : October 2019  
Conference date : 16 October 2019

Looking forward to seeing you in our conference.  
Thank you.

**ATM BNI**

30/08/19 12:50 S1DUDS11IK  
KK PIP

\*\*\*\*220133185714

NO. REKORD 2277

PEMBAYARAN VIRTUAL ACCOUNT BILLING

NO.VA 8581190827122803

NAMA DARUL PRAYOGO

TOTAL TAGIHAN RP1.500.000

BIAYA ADMIN RPO

TOTAL BAYAR RP 1.500.000

SIMPAN RESI INI  
SEBAGAI BUKTI TRANSAKSI YANG SAH

KUNJUNGI [www.bni.co.id](http://www.bni.co.id)  
UNTUK INFORMASI PROMO-PROMO MENARIK



## PAYMENT RECEIPT

Date : 16 Oktober 2019

Number : 041/02/EIC/X/2019

Name : Darul Prayogo

Institution : Politeknik Ilmu Pelayaran Semarang

Category :  Author/ Presenter

Co - author

Mini-symposium

Participant

Amount : IDR 1.500.000

Semarang, 16 Oktober 2019



**FEDDY SETIO PRIBADI S.Pd., MT.**

Chief of EIC 2019