

Lampiran 5

Ship's Particular

SHIP PARTICULARS

NAME OF VESSEL		G A N D I N I		DIMENSION	
CALL SIGN		P N G S		L.O.A	179.900 M
FLAG		INDONESIA		L.B.P	171.000 M
PORT REGISTRY		JAKARTA		BREADTH (mld)	31.000 M
CLASSIFICATION		NIPPON KAIJI KYOKAI		DEPTH (mld)	15.900 M
IMO NUMBER		9 1 8 0 0 9 7		DRAFT (dsgn)	9.000 M
OFFICIAL NUMBER		3 8 9 5 1 7		HEIGHT (overall)	43.428 M
SHIP KIND OF SERVICE		OIL TANKER (WHITE PRODUCT)		HEIGHT (keel-W/H)	27.200 M
BUILDER		DAEWOO SHIPYARD -		TONNAGE	
		SOUTH KOREA		GRT	23.328 GRT-INT
KEEL LYING		JUNE 11 th , 1998		NRT	7.356 GRT-INT
LAUNCHING		SEPTEMBER 05 th , 1998		COMPLEMENT	
NAME OF ONWNER		PT. RUBY MARITIME PTE, LTD		26 PERSONS	
SHIP OPERATOR		PT. GBLT JAKARTA		SERVICE SPEED	
INMARSAT C.ID No		452501556		14.0 Knots at NRC with 15 % S.M	
MMSI No		525007035		ANCHOR CHAIN	
SAT TEL		+ 870773210101		P/S ANCHOR = 11 AND S/S ANCHOR = 12	
EMAIL		PNGS@globeemail.com		LAST DRY DOCK	
EMAIL-L		452501556@in.mail65.com.sg		NOVEMBER 2011	
RADIO Adm - QRC		MARCONI LONDON - GB08		Company IMO No : 5473165	
				Change Flag Date : Dec, 29th '2009	
DEAD WEIGHT					
MARK ZONE		FREEBOARD (Meter)	DRAFT (EXT) (Meter)	DISPLACEMENT (Tonnes)	DEADWEIGHT (Tonnes)
TF	TROPICAL FRESH WATER	6.552	9.408	39,903	32,023
F	FRESH WATER	6.710	9.220	39,023	31,143
T	TROPICAL	5.726	9.204	39,922	32,024
S	SUMMER	5.914	9.016	39,024	31,144
W	WINTER	6.102	8.828	38,130	30,250
MACHINERY EQUIPMENT					
STEERING GEAR	1	TYPE: ROTARY VANE S/G CAP : 51 OKNM B&W 5550MC, 2 STROKE DIRECT REVERSIBLE			
MAIN ENGINE	1	MCR 9, 000 BHP x 118.0 RPM MVR 8, 100 BHP x 113.9 RPM			
PROPELLER	1	FIXED PITCH, NI-AL BRONZE DIA 8.20 Mtrs, BLADE 4			
AUX. BOILER	1	VERTICAL OIL FIRED CAP : 3TON/H			
DIESEL GENERATOR ENGINE	3	4 - CYCLE, VERT, SINGLE T/C 1.319 BHP x 900 RPM			
EM/CY GENERATOR ENGINE	1	4 - STROKE, TRUNK PISTON, F.W COOLED 120 KW x 1,800 RPM			
FRESH WATER GENERATOR	1	M/E WASTE . CAP : 15 TON/DAY AT NCR OF M/E			
CARGO OIL TANK					
CARGO TANK COATING		PURE EPOXY			
CARGO TANK CAPACITY 98%		39032 Cu.M			
PUMP					
CARGO PUMP	3	MOTOR DRIVEN CENTRIFUGAL 1,200 Cu.M/HOUR x 125 MTH			
CARGO STRIPPING PUMP	1	MOTOR DRIVEN HORIZONTAL TWIN SCREW TYPE 150 Cu. M/HOUR x 125 MTH			
BALLAST PUMP	1	ELECTRIC MOTOR DRIVEN CENTRIFUGAL 1,200 Cu.M/HOUR x 25 MTH			
EMERGENCY FIRE PUMP	1	ELECTRIC MOTOR DRIVEN VERTICAL CENTRIFUGAL 72 Cu.M/HOUR x 80 MTH			
BILGE, FIRE & G.S PUMP	2	ELECTRIC MOTOR DRIVEN VERTICAL 120/240 Cu. M/H x 90/45 MTH			

